

FIX-A-CHIP INSTRUCTIONS

CONTENTS OF KIT: 7 Intermixable colors compound, mixing bottles, clear finish, grain packet, brush, sandpaper.

Clean off the damaged area to be repaired. Remove any splinters by lightly sanding the area evenly.

The color repair compounds are intermixable. Using the color match guide, mix the desired combination of colors into the labeled mixing bottle.

Apply the repair compound directly on the damaged area in layers. Allow each layer to dry before applying the next layer. Spread the compound as evenly as possible, removing any excess with the spatula in your kit.

On the final layer, if a grained or pattern surface is desired, cover the wet compound with one of the grain papers in the kit. Pick the correct grain by turning it over and looking to see which grain texture matches your area. Apply some Vaseline on the bottom side of the grain paper (to keep it from sticking to the compound) tape it down, and press lightly on the paper to imprint the texture into the wet compound.

Allow your repair to dry overnight. When dry, carefully peel off the grain paper and examine the repair. The repaired spot may be filled as often as necessary to bring it up to the undamaged laminate or to refill any defects. After the repair is finished and dry, it may be lightly sanded. Clear finish or a floor wax may be applied for a shinier finish.

Wood grain and antique effects can be achieved by first applying the lighter color, and then the darker color. Use a toothpick to draw lines over the repaired area, and the darker compound.

If you have any questions or problems, feel free to call the number below.

Repair Products Unlimited, Inc. 1021 Evans Ave., Akron OH. 44305

Phone: 330 798-0441 Fax: 330 798-0447

Email: Liqleather@aol.com

Website: www.repair-it-all.com